


## Use Advantages

Used as a general purpose diode in power supplies, or in clipping and steering applications. Operation at temperatures up to 200 degrees C, no derating. Can be used in harsh environments where hermeticity and low cost are important. Compatible with all major automatic pick and place mounting equipment. May be used on ceramic boards along with high temperature IR solder reflow.

## Features

- Humidity proof glass
- Thermally matched system
- No thermal fatigue
- No applications restrictions
- Sigma Bond™ plated contacts
- 100% guaranteed solderability
- Problem free assembly
- Six Sigma quality
- LL-35 MiniMELF types available



Absolute Maximum Ratings	Symbol	Value	Unit
Average Forward Rectified Current at $T_{Ambient} = 25^{\circ}C$	$I_{AV}$	0.65	Amp
Maximum Non-Repetitive Surge (8.3 mSecs. 1/2 sine)	$I_{FSM}$	2.0	Amps
Junction Temperature Range	$T_J$	-65 to +200	$^{\circ}C$
Storage Temperature Range	$T_S$	-55 to +200	$^{\circ}C$
Max. Average Power Dissipation	$P_{diss}$	250	mW

### Characteristics at $T = 25^{\circ}C$

Type	Peak Inverse Voltage (MIN.) (PIV)	Maximum Average Rectified Current ( $I_O$ )	Maximum Forward Voltage Drop ( $V_F$ ) @ 0.1A	Maximum Leakage Current ( $I_R$ ) @ PIV		Minimum Saturation Voltage (@0.1 mA)
	Volts	Amps	Volts	25 $^{\circ}C$ $\mu A$	150 $^{\circ}C$ $\mu A$	Volts
1N482B	30	0.2	1.0	0.025	5	40
1N483B	60	0.2	1.0	0.025	5	80
1N484B	125	0.2	1.0	0.025	5	150
1N485B	175	0.2	1.0	0.025	5	200
1N486B	225	0.2	1.0	0.025	5	250

LL-35 Glass miniMELF package available, substitute an LL prefix instead of "1N"..