

2N5397, 2N5398**N-Channel Silicon Junction Field-Effect Transistor**

- Low-Noise
- High Power Gain
- High Transconductance
- Mixers
- Oscillators
- VHF Amplifiers

Absolute maximum ratings at $T_A = 25^\circ\text{C}$

Reverse Gate Source & Reverse Gate Drain Voltage	- 25 V
Drain Source Voltage	25 V
Continuous Forward Gate Current	10 mA
Continuous Device Power Dissipation	300 mW
Power Derating	1.7 mW/ $^\circ\text{C}$

At 25°C free air temperature:

Static Electrical Characteristics

	2N5397	2N5398		Process NJ26L		
		Min	Max	Unit	Test Conditions	
Gate Source Breakdown Voltage	$V_{(\text{BR})\text{GSS}}$	- 25		V	$I_G = - 1 \mu\text{A}, V_{DS} = \emptyset\text{V}$	
Gate Source Forward Voltage	$V_{GS(F)}$		1	V	$I_G = 1 \text{ mA}, V_{DS} = \emptyset\text{V}$	
Gate Reverse Current	I_{GSS}		- 0.1	nA	$V_{GS} = - 15 \text{ V}, V_{DS} = \emptyset\text{V}$	
			- 0.1	μA	$V_{GS} = - 15 \text{ V}, V_{DS} = \emptyset\text{V}$	$T_A = 150^\circ\text{C}$
Gate Source Cutoff Voltage	$V_{GS(\text{OFF})}$	- 1	- 6	V	$V_{DS} = 10 \text{ V}, I_D = 1 \text{ nA}$	
Drain Saturation Current (Pulsed)	I_{DSS}	10	30	5	40	mA
					$V_{DS} = 10 \text{ V}, V_{GS} = \emptyset\text{V}$	

Dynamic Electrical Characteristics

Common Source Forward Transconductance	g_{fs}	5.5	9	5	10	mS	$V_{DG} = 10 \text{ V}, I_D = 10 \text{ mA}$	$f = 450 \text{ MHz}$
Common Source Forward Transfer Admittance	$ Y_{fs} $	6	10	5.5	10	mS	$V_{DS} = 10 \text{ V}, I_D = 10 \text{ mA}$	$f = 1 \text{ kHz}$
Common Source Output Conductance	$ g_{os} $		0.4		0.5	mS	$V_{DG} = 10 \text{ V}, I_D = 10 \text{ mA}$	$f = 450 \text{ MHz}$
Common Source Input Admittance	$ Y_{os} $		0.2		0.4	mS	$V_{DS} = 10 \text{ V}, I_D = 10 \text{ mA}$	$f = 1 \text{ kHz}$
Common Source Input Conductance	g_{is}		2		3	mS	$V_{DG} = 10 \text{ V}, I_D = 10 \text{ mA}$	$f = 450 \text{ MHz}$
Common Source Input Capacitance	C_{iss}		5		5.5	pF	$V_{DG} = 15 \text{ V}, V_{GS} = \emptyset\text{V}$	$f = 1 \text{ kHz}$
Common Source Reverse Transfer Capacitance	C_{rss}		1.2		1.3	pF	$V_{DG} = 15 \text{ V}, V_{GS} = \emptyset\text{V}$	$f = 1 \text{ kHz}$

TO-72 Package

Dimensions in Inches (mm)

Pin Configuration

1 Source, 2 Drain, 3 Gate, 4 Case

Surface Mount

SMP5397, SMP5398



1000 N. Shiloh Road, Garland, TX 75042
 (972) 487-1287 FAX (972) 276-3375

www.interfet.com