

## 2N5460, 2N5461, 2N5462

## P-Channel Silicon Junction Field-Effect Transistor

- Audio Amplifiers
- General Purpose Amplifiers

## Absolute maximum ratings at 25 °C

Reverse Gate Source & Reverse Gate Drain Voltage	40 V
Continuous Forward Gate Current	- 10 mA
Continuous Device Power Dissipation	310 mW
Power Derating	2.8 mW/°C

At 25°C free air temperature:  
Static Electrical Characteristics

		2N5460		2N5461		2N5462		Process PJ32	
		Min	Max	Min	Max	Min	Max	Unit	Test Conditions
Gate Source Breakdown Voltage	$V_{(BR)GSS}$	40		40		40		V	$I_G = 10 \mu A, V_{DS} = 0V$
Gate Reverse Current	$I_{GSS}$		5		5		5	nA	$V_{GS} = 20V, V_{DS} = 0V$
			1		1		1	$\mu A$	$V_{GS} = 20V, V_{DS} = 0V$
Gate Source Cutoff Voltage	$V_{GS(OFF)}$	0.75	6	1	7.5	1.8	9	V	$V_{DS} = -15V, I_D = -1 \mu A$
Gate Source Voltage	$V_{GS}$	0.8	4.5					V	$V_{DS} = -15V, I_D = -100 \mu A$
				0.8	4.5			V	$V_{DS} = -15V, I_D = -200 \mu A$
						1.5	6	V	$V_{DS} = -15V, I_D = -400 \mu A$
Drain Saturation Current (Pulsed)	$I_{DSS}$	- 1	- 5	- 2	- 9	- 4	- 16	mA	$V_{DS} = -15V, V_{GS} = 0V$

## Dynamic Electrical Characteristics

Drain Source ON Resistance	$r_{ds(on)}$		2		0.8		0.4	k $\Omega$	$V_{GS} = 0V, I_D = 0A$	f = 1 kHz
Common Source Forward Transadmittance	$ Y_{fs} $	1	4	1.5	5	2	6	mS	$V_{DS} = -15V, V_{GS} = 0V$	f = 1 kHz
Common Source Output Admittance	$ Y_{os} $		75		75		75	$\mu S$	$V_{DS} = -15V, V_{GS} = 0V$	f = 1 kHz
Common Source Input Capacitance	$C_{iss}$		7		7		7	pF	$V_{DS} = -15V, V_{GS} = 0V$	f = 1 MHz
Common Source Reverse Transfer Capacitance	$C_{rss}$		2		2		2	pF	$V_{DS} = -15V, V_{GS} = 0V$	f = 1 MHz
Equivalent Short Circuit Input Noise Voltage	$\bar{e}_N$		2.5		2.5		2.5	dB	$V_{DS} = -15V, V_{GS} = 0V$	f = 100 Hz, BW = 1 Hz
Noise Figure	NF		115		115		115	nV/ $\sqrt{Hz}$	$V_{DS} = -15V, V_{GS} = 0V,$ $R_G = 1M\Omega$	f = 100 Hz

## TO-226AA Package

Dimensions in Inches (mm)

## Pin Configuration

1 Drain, 2 Source, 3 Gate

## Surface Mount

SMP5460, SMP5461, SMP5462

[www.interfet.com](http://www.interfet.com)
 InterFET Corporation

 1000 N. Shiloh Road, Garland, TX 75042  
 (972) 487-1287 FAX (972) 276-3375