


1N6774, JANTX1N6774, JANTXV1N6774
 1N6775, JANTX1N6775, JANTXV1N6775
 1N6776, JANTX1N6776, JANTXV1N6776
 1N6777, JANTX1N6777, JANTXV1N6777

JANTX, JANTXV POWER RECTIFIERS, SINGLE TO-257AA PACKAGE, QUALIFIED TO MIL-PRF-



50V Thru 200V, 15A, Ultra-Fast Power Rectifiers in a TO-257AA Hermetic 2 Pin Package


FEATURES

- High Current
- Isolated and Hermetically Sealed
- Low V_F
- Ultra-Fast
- Small Size
- Qualified to MIL-PRF-19500/646

DESCRIPTION


This hermetically packaged QPL product features the latest advanced silicon and packaging technology. It is ideally suited for Military low voltage rectifier requirements where small size, high performance and high reliability are required, and in applications such as switching power supplies, motor controls, inverters, choppers, audio amplifiers and high energy pulse circuits.

SCHEMATIC



1 = Cathode
 2 = Anode

MECHANICAL OUTLINE



TO-257AA
 2-Pin

1N6774, JANTX1N6774, JANTXV1N6774
 1N6775, JANTX1N6775, JANTXV1N6775
 1N6776, JANTX1N6776, JANTXV1N6776
 1N6777, JANTX1N6777, JANTXV1N6777

PRIMARY ELECTRICAL CHARACTERISTICS

MAXIMUM RATINGS @ 25°C Per Diode, Per MIL-PRF-19500/646

MIL-PRF 19500	PART NUMBER	V _{RWM} Volts	I _F Amps T _C = 100 C	I _F Surge 8.3 mSec	R _{θJC}	Operating Temp Range
646	1N6774	50V	15 A	180 A	2.0 C/W	-65 C to + 150 C
646	1N6775	100V	15 A	180 A	2.0 C/W	-65 C to + 150 C
646	1N6776	150V	15 A	180 A	2.0 C/W	-65 C to + 150 C
646	1N6777	200V	15 A	180 A	2.0 C/W	-65 C to + 150 C

ELECTRICAL CHARACTERISTICS @ 25°C Per Diode, Per MIL-PRF-19500/646

MIL-PRF 19500	PART NUMBER	V _F @ 8 A	V _F @ 15 A	I _k @ 25 C	I _k @ 100 C	t _{RR} I _F = 1.0A, di/dt = 50A/ua	C _J f = 1.0 MHz
646	1N6774	1.0V	1.15 V	10 μa	500 μa	35 nsec	300 pF
646	1N6775	1.0V	1.15 V	10 μa	500 μa	35 nsec	300 pF
646	1N6776	1.0V	1.15 V	10 μa	500 μa	35 nsec	300 pF
646	1N6777	1.0V	1.15 V	10 μa	500 μa	35 nsec	300 pF

PRIMARY ELECTRICAL CHARACTERISTICS @ T_C = 25 C

MIL-PRF 19500	PART NUMBER	V _{RWM} , Volts	V _F @ 15A	I _F Amps @ T _C = 100 C
646	1N6774	50V	1.15V	15
646	1N6775	100V	1.15V	15
646	1N6776	150V	1.15V	15
646	1N6777	200V	1.15V	15