

Type 2N2484
Geometry 0220 / 0307
Polarity NPN
Qual Level: Pending

Generic Part Number:
2N2484

REF: MIL-PRF-19500/376

Features:

[Request Quotation](#)

- General-purpose high gain, low power transistor which operates over a wide temperature range.
- Housed in a [TO-18](#) case.
- Also available in chip form using the 0220 / [0307](#) chip geometry.
- The Min and Max limits shown are per [MIL-PRF-19500/376](#) which Semicoa meets in all cases.



Maximum Ratings

$T_C = 25^{\circ}\text{C}$ unless otherwise specified

| Rating | Symbol | Rating | Unit |
|--------------------------------|-----------|-------------|--------------------|
| Collector-Emitter Voltage | V_{CEO} | 60 | V |
| Collector-Base Voltage | V_{CBO} | 60 | V |
| Emitter-Base Voltage | V_{EBO} | 6.0 | V |
| Collector Current, Continuous | I_C | 50 | mA |
| Operating Junction Temperature | T_J | -65 to +200 | $^{\circ}\text{C}$ |
| Storage Temperature | T_{STG} | -65 to +200 | $^{\circ}\text{C}$ |

Electrical Characteristics

$T_C = 25^\circ\text{C}$ unless otherwise specified

| OFF Characteristics | Symbol | Min | Max | Unit |
|---|---------------|-----|-----|---------------|
| Collector-Base Breakdown Voltage $I_C = 10 \mu\text{A}$ | $V_{(BR)CBO}$ | 60 | --- | V |
| Collector-Emitter Breakdown Voltage $I_C = 10 \text{mA}$ | $V_{(BR)CEO}$ | 60 | --- | V |
| Emitter-Base Breakdown Voltage $I_E = 10 \mu\text{A}$ | $V_{(BR)EBO}$ | 6.0 | --- | V |
| Collector-Base Cutoff Current $V_{CB} = 45 \text{V}$ | I_{CBO1} | --- | 5 | nA |
| $V_{CB} = 45 \text{V}, T_A = +150^\circ\text{C}$ | I_{CBO2} | --- | 10 | μA |
| Emitter-Base Cutoff Current $V_{EB} = 5.0 \text{V}$ | I_{EBO} | --- | 2 | nA |
| Collector-Emitter Cutoff Current $V_{CE} = 5 \text{V}$ | I_{CEO} | --- | 2 | nA |
| $V_{CE} = 45 \text{V}$ | I_{CES} | --- | 5 | nA |

| ON Characteristics | Symbol | Min | Max | Unit |
|---|---------------|-----|-----|------|
| DC Current Gain | | | | |
| $I_C = 1 \mu\text{A}, V_{CE} = 5 \text{V}$ | h_{FE1} | 45 | --- | --- |
| $I_C = 10 \mu\text{A}, V_{CE} = 5 \text{V}$ | h_{FE2} | 200 | 500 | --- |
| $I_C = 100 \mu\text{A}, V_{CE} = 5 \text{V}$ | h_{FE3} | 225 | 675 | --- |
| $I_C = 500 \mu\text{A}, V_{CE} = 5 \text{V}$ | h_{FE4} | 250 | 800 | --- |
| $I_C = 1 \text{mA}, V_{CE} = 5 \text{V}$ | h_{FE5} | 250 | 800 | --- |
| $I_C = 10 \text{mA}, V_{CE} = 5 \text{V}$ (pulsed) | h_{FE6} | 225 | 800 | --- |
| $I_C = 10 \mu\text{A}, V_{CE} = 5 \text{V}, T_A = -55^\circ\text{C}$ | h_{FE7} | 35 | --- | --- |
| Collector-Emitter Saturation Voltage Saturated $I_C = 150 \text{mA}, I_B = 100 \mu\text{A}$ | $V_{CE(sat)}$ | --- | 0.3 | V dc |
| Base-Emitter Saturation Voltage Non Saturated $V_{CE} = 5 \text{V}, I_C = 100 \mu\text{A}$ | V_{BE} | 0.5 | 0.7 | V dc |

| Small Signal Characteristics | Symbol | Min | Max | Unit |
|---|-------------|-----|--------------------|------------------|
| <i>Magnitude of Short-Circuit</i> | | | | |
| <i>Forward Current Transfer Ratio</i> | | | | |
| $V_{CE} = 5\text{ V}, I_C = 50\ \mu\text{A}, f = 5\text{ MHz}$ | $ h_{FE} 1$ | 3.0 | --- | --- |
| $V_{CE} = 5\text{ V}, I_C = 500\ \mu\text{A}, f = 30\text{ MHz}$ | $ h_{FE} 2$ | 2.0 | 7.0 | --- |
| <i>Open Circuit Output Admittance</i> | | | | |
| $V_{CE} = 5\text{ V}, I_C = 1\text{ mA}, f = 1\text{ kHz}$ | hoe | --- | 40 | μohms |
| <i>Open-Circuit, Reverse Voltage Transfer Ratio</i> | | | | |
| $V_{CE} = 5\text{ V}, I_C = 1\text{ mA}, f = 1\text{ kHz}$ | h_{RE} | --- | 8×10^{-4} | --- |
| <i>Short-Circuit Input Impedance</i> | | | | |
| $V_{CE} = 5\text{ V}, I_C = 1\text{ mA}, f = 1\text{ kHz}$ | h_{IE} | 3.5 | 24 | ohms |
| <i>Short Circuit Forward Current Transfer Ratio</i> | | | | |
| $V_{CE} = 5\text{ V}, I_C = 1\text{ mA}, f = 1\text{ kHz}$ | h_{FE} | 250 | 900 | --- |
| <i>Open Circuit Output Capacitance</i> | | | | |
| $V_{CB} = 5\text{ V}, I_E = 0, 100\text{ kHz} < f < 1\text{ MHz}$ | C_{OBO} | --- | 5.0 | pF |
| <i>Input Capacitance, Output Open Circuited</i> | | | | |
| $V_{EB} = 0.5\text{ V}, I_C = 0, 100\text{ kHz} < f < 1\text{ MHz}$ | C_{IBO} | --- | 6.0 | pF |
| <i>Noise Figure</i> | | | | |
| $f = 100\text{ Hz}, V_{CE} = 5\text{ V}, I_C = 10\ \mu\text{A}, R_g = 10\text{ kohm}$ | F1 | --- | 7.5 | dB |
| $f = 1\text{ kHz}, V_{CE} = 5\text{ V}, I_C = 10\ \mu\text{A}, R_g = 10\text{ kohm}$ | F2 | --- | 3 | dB |
| $f = 10\text{ kHz}, V_{CE} = 5\text{ V}, I_C = 10\ \mu\text{A}, R_g = 10\text{ kohm}$ | F3 | --- | 2 | dB |
| $f = 10\text{ Hz to } 15.7\text{ kHz}, V_{CE} = 5\text{ V}, I_C = 10\ \mu\text{A}, R_g = 10\text{ kohm (wideband noise)}$ | F4 | --- | 3 | dB |